



Fire Rating



Low Leakage



Ships In 3 Days
Or Less *

IN-STOCK HYDRO1® FLOOD DOOR (SINGLE)

THIS FLOOD-PROOF DOOR SHIPS IN 3 DAYS OR LESS*

The in-stock Hydro1® Flood Door provides passive flood protection that has passed testing for Florida Product Approval, including the High Velocity Hurricane Zone (Miami-Dade and Broward counties) - FL #39631. Sized to fit standard building openings 40" to 41.5" wide and a minimum of 86" tall, this door features a patented design, is easy to install, provides the lowest leakage rate in the industry and is independent-party witness tested to the ANSI/FM Approvals 2510-2020 4.3.3 standard up to 8 feet of water protection height. Once it's installed, it's always in place, providing 24-hour flood protection while still allowing access to your facility.

UNBEATABLE FLOOD PROTECTION, EVEN WHEN YOU'RE IN A HURRY

- Ships in 3 days or less; limited to stock on hand
- Passed Florida Product Approval testing, including approval for the High Velocity Hurricane Zone (Miami-Dade and Broward counties). FL #39631
- Wind driven rain/water infiltration test passed
- Lowest leakage rate in the industry; includes leakage through the entire product assembly including hardware and lockset
- Independent-party witness factory tested to 3' and 8' water protection heights
- 90 min. fire rated – positive pressure endurance test criteria per UL10C
- ADA compliant

ENGINEERED TO FIT JUST RIGHT

- Standard 3'x7' door panel
- Available in single door only with a right-hand reverse or left-hand reverse option
- Easy to install
- One-piece perimeter gasket creates a forgiving, watertight seal
- Finish: one coat primer, two coats industrial enamel, ANSI 70 Gray

[See stock door Tech-Data for loading capacity and technical details.](#)



Ask about our other Hydro1® line of custom-size flood doors available in single or paired configurations:



Hydro1® Pedestrian
Flood Door



Hydro1® 90 Min.
Fire Rated Flood Door



Hydro1® Mechanical
Room Flood Door

* Limited to stock on hand.